

288 Commander P.I.G.

CAPACITY

MAX. WEIGHT CAPACITY	YACHT CERTIFICATION			
PERSONS (QUANTITY) (SEATING FOR 11)	YACHT CERTIFICATION			
PERSONS (LBS.)	YACHT CERTIFICATION			
MAX H.P.	600	HP	447	KW

SPECIFICATION

L.O.A.	336	IN	28'-0"/ 8.5M	FT/M
L.W.L.	272	IN	22'-6"/ 6.9M	FT/M
BEAM	116	IN	9'8"/ 2.9M	FT/M
DEAD RISE	18	DEG		
DEAD RISE BOW ENTRY POINT	40.5	DEG		
TRANSOM ANGLE	15	DEG		
STATIC FLOAT ANGLE (KEEL TO BOW)	1	DEG		
TRANSOM HEIGHT (Center line)	30 (25 @ engine)	IN	0.76	METER
TRANSOM WIDTH	105.5	IN	2.68	METER
COCKPIT DEPTH AFT	27	IN	0.69	METER
COCKPIT DEPTH BOW	36	IN	0.91	METER
FREEBOARD AFT	34	IN	0.86	METER
FREEBOARD BOW (BOW TO WATER LINE TROLLING MOTOR)	49	IN	1.24	METER
DRAFT (HULL)	18	IN	0.46	METER
DEPTH (KEEL TO TOP OF GUNNEL)	66	IN	1.68	METER
CENTER OF GRAVITY FROM KEEL/TRANSOM	118	IN	3.00	METER
HEIGHT, KEEL TO TOP	118	IN	3.00	METER
HEIGHT, KEEL TO TOP- (w/ outriggers)	121	IN	3.07	METER
HEIGHT, KEEL TO TOP- (w/ Radar)	122	IN	3.10	METER
BRIDGE CLEARANCE W/TOPMAX	100	IN	2.54	METER
CABIN HEIGHT	71	IN	1.80	METER
DRY WEIGHT BOAT: w/ options but no Gear, Batteries, Fluids, or Motor(s)	6278	LBS.	2848	KG
WEIGHT BOAT (Options and Motor(s) no Fluids)	7959	LBS.	3610	KG
MAX. WEIGHT BOAT: w/batteries, Fluids, gear, largest Motor(s)	9793	LBS.	4442	KG
BATTERY QUANTITY	4	EA	1-LE,1-RE,1-H,1-BKP	
PANEL SIZE FOR ELECTRONICS	35W X 13.5H (Standard 2 12" Garmin)			

TUB CAPACITY

ROPE LOCKER	14	CF	34"L, 62"W,31"D	
TUB BOW PORT	122.5	QT	36"L, 14"W, 13"D	
TUB BOW STARBOARD	122.5	QT	36"L, 14"W, 13"D	
TUB BOW FLOOR (bucket)	60	QT	15"L,14"W, 14"D	
TUB CONSOLE LOUNGER	10.5	CF	29"L,40"W,19"H	
TUB FISH AFT PORT	160	QT	85"L,17"W,12"D	
TUB FISH AFT STBD	180	QT	65"L,17"W,12"D	
TUB BAITWELL AFT PORT	30	GAL	20"L,18"W,24"D	
TUB BAITWELL AFT CENTER	45	GAL	11"L, 38"W, 26"D	
TUB STORAGE AFT STBD SEAT	2.36	CF	16.5L,16.5W,15D	
COOLER SIZE (REMOVABLE)	65	QT	YETI	

TANK CAPACITY

FUEL TANK	185	GAL	700	LITER
FUEL SENDER	19"	INCH	NA	NA
FRESH WATER	24	GAL	91	LITER
HOLDING TANK	12	GAL	45	LITER